



RULES

PUBLICATION 5/P

REQUIREMENTS FOR TURBOCHARGERS

January
2023

Publications P (Additional Rule Requirements) issued by Polski Rejestr Statków complete or extend the Rules and are mandatory where applicable.

GDAŃSK

Publication No. 5/P – Requirements for turbochargers – January 2023 is based on IACS Unified Requirements M73 (Rev.1 March 2022).

The requirements of UR M73 Rev.1, except for M73.4 (Certification), are to be uniformly implemented to turbochargers with the date of application for certification on or after 1 January 2023. Turbochargers with an existing type approval on 1 January 2023 are not required to be re-type approved in accordance with this UR until the current Type Approval reaches its expiry date.

The requirements of M73.4 Rev.1 are to be uniformly implemented to turbochargers with the date of application for certification of an individual turbocharger on or after 1 January 2023.

The “date of application for certification” is the date of whatever document the PRS requires/accepts as an application or request for certification of a new turbocharger type or of a turbocharger type that has undergone substantive modifications in respect of the one previously type approved, or for renewal of an expired type approval certificate.

This Publication was approved by the PRS S.A. Board on 28 December 2022 and enters into force on 1 January 2023.

© Copyright by Polish Register of Shipping*, 2023

* *Polish Register of Shipping means Polski Rejestr Statków S.A., seated in Gdańsk, al. gen. Józefa Hallera 126, 80-416 Gdańsk, Poland, registered in the Register of Entrepreneurs of the National Court Register, under entry number 0000019880. Polish Register of Shipping, its affiliates and subsidiaries, their respective officers, employees or agents are, individually and collectively, referred to as Polish Register of Shipping or as PRS for short.*

CONTENTS

	Page
1 Scope	5
2 Documentation to be submitted	5
2.1 Category A:.....	5
2.2 Category B and C:.....	5
2.3 Category C:.....	6
3 Design requirements and corresponding type testing	6
3.1 General.....	6
3.2 Containment.....	6
3.3 Disc-shaft shrinkage fit.....	7
3.4 Type testing.....	7
4 Certification	7
5 Alarms AND Monitoring	8

1 SCOPE

1.1 These requirements are applicable for turbochargers with regard to design approval, type testing and certification and their matching on engines.

Turbochargers are to be type approved, either separately or as a part of an engine. The requirements are written for exhaust gas driven turbochargers, but apply in principle also for engine driven chargers.

1.2 The requirements escalate with the size of the turbochargers. The parameter for size is the engine power (at MCR) supplied by a group of cylinders served by the actual turbocharger, (e.g. for a V-engine with one turbocharger for each bank the size is half of the total engine power).

1.3 Turbochargers are categorised in three groups depending on served power by cylinder groups with:

- Category A: ≤ 1000 kW
- Category B: > 1000 kW and ≤ 2500 kW
- Category C: > 2500 kW

2 DOCUMENTATION TO BE SUBMITTED

2.1 Category A:

On request

- Containment test report.
- Cross sectional drawing with principal dimensions and names of components.
- Test program.

2.2 Category B and C:

- Cross sectional drawing with principal dimensions and materials of housing components for containment evaluation.
- Documentation of containment in the event of disc fracture, see p. 3.2
- Operational data and limitations as:
 - Maximum permissible operating speed (rpm)
 - Alarm level for over-speed
 - Maximum permissible exhaust gas temperature before turbine
 - Alarm level for exhaust gas temperature before turbine
 - Minimum lubrication oil inlet pressure
 - Lubrication oil inlet pressure low alarm set point
 - Maximum lubrication oil outlet temperature
 - Lubrication oil outlet temperature high alarm set point
 - Maximum permissible vibration levels, i.e. self- and externally generated vibration

(Alarm levels may be equal to permissible limits but shall not be reached when operating the engine at 110% power or at any approved intermittent overload beyond the 110%.)

- Arrangement of lubrication system, all variants within a range
- Type test reports
- Test program

2.3 Category C:

- Drawings of the housing and rotating parts including details of blade fixing.
- Material specifications (chemical composition and mechanical properties) of all parts mentioned above.
- Welding details and welding procedure of above mentioned parts, if applicable.
- Documentation¹⁾ of safe torque transmission when the disc is connected to the shaft by an interference fit, see p. 3.3.
- Information on expected lifespan, considering creep, low cycle fatigue and high cycle fatigue.
- Operation and maintenance manuals¹⁾.

3 DESIGN REQUIREMENTS AND CORRESPONDING TYPE TESTING

3.1 General

3.1.1 The turbochargers shall be designed to operate under conditions given in PRS Rules for the Classification and Construction of Sea-going Ships: Part VI – chapter 1.6 and Part VII – chapter 2.1. The component lifetime and the alarm level for speed shall be based on 45°C air inlet temperature.

3.1.2 The air inlet of turbochargers shall be fitted with a filter.

3.2 Containment

3.2.1 Turbochargers shall fulfil containment in the event of a rotor burst. This means that at a rotor burst no part may penetrate the casing of the turbocharger or escape through the air intake. For documentation purposes (test/calculation), it shall be assumed that the discs disintegrate in the worst possible way.

3.2.2 For category B and C, containment shall be documented by testing. Fulfilment of this requirement can be awarded to a generic range² of turbochargers based on testing of one specific unit. Testing of a large unit is preferred as this is considered conservative for all smaller units in the generic range. In any case, it must be documented (e.g. by calculation) that the selected test unit really is representative for the whole generic range.

3.2.3 The minimum test speeds, relative to the maximum permissible operating speed, are:

- For the compressor:120%.
- For the turbine:140% or the natural burst speed, whichever is lower.

3.2.4 Containment tests shall be performed at working temperature.

3.2.5 A numerical analysis (simulation) of sufficient containment integrity of the casing based on calculations by means of a simulation model may be accepted in lieu of the practical containment test, provided that:

- The numerical simulation model has been tested and its suitability/accuracy has been proven by direct comparison between calculation results and the practical containment test for a reference application (reference containment test). This test shall be performed at least once by the manufacturer for acceptance of the numerical simulation method in lieu of tests.

¹⁾ Applicable to two sizes in a generic range of turbochargers

² A generic range means a series of turbocharger which are of the same design, but scaled to each other.

- The corresponding numerical simulation for the containment is performed for the same speeds as specified for the containment test.
- Material properties for high-speed deformations are to be applied in the numeric simulation. The correlation between normal properties and the properties at the pertinent deformation speed are to be substantiated.
- The design of the turbocharger regarding geometry and kinematics is similar to the turbocharger that was used for the reference containment test. In general, totally new designs will call for a new reference containment test.

3.3 Disc-shaft shrinkage fit

3.3.1 Applicable to Category C

3.3.1.1 In cases where the disc is connected to the shaft with interference fit, calculations shall substantiate safe torque transmission during all relevant operating conditions such as maximum speed, maximum torque and maximum temperature gradient combined with minimum shrinkage amount.

3.4 Type testing

3.4.1 Applicable to Categories B and C.

3.4.2 The type test for a generic range of turbochargers may be carried out either on an engine (for which the turbocharger is foreseen) or in a test rig.

3.4.3 Turbochargers are to be subjected to at least 500 load cycles at the limits of operation. This test may be waived if the turbocharger together with the engine is subjected to this kind of low cycle testing, conducted by according applicable PRS requirements for internal combustion engines given in PRS Publication no 28/P (as per ref. requirement given in a new IACS UR M71).

3.4.4 The suitability of the turbocharger for such kind of operation is to be preliminarily stated by the manufacturer.

3.4.5 The rotor vibration characteristics shall be measured and recorded in order to identify possible sub-synchronous vibrations and resonances.

3.4.6 The type test shall be completed by a hot running test at maximum permissible speed combined with maximum permissible temperature for at least one hour. After this test, the turbocharger shall be opened for examination, with focus on possible rubbing and the bearing conditions.

3.4.7 The extent of the surveyor presence during the various parts of the type tests is left to the discretion of PRS.

4 CERTIFICATION

4.1 The manufacturer shall adhere to a quality system designed to ensure that the designer specifications are met, and that manufacturing is in accordance with the approved drawings.

4.2 For category C, this shall be verified by means of periodic product audits of an Alternative Certification Scheme (ACS) by the PRS acc to the requirement given in Publ. PRS 115/P.

4.3 These audits shall focus on:

- Chemical composition of material for the rotating parts
- Mechanical properties of the material of a representative specimen for the rotating parts and the casing.
- UT and crack detection of rotating parts
- Dimensional inspection of rotating parts.
- Rotor balancing
- Hydraulic testing of cooling spaces to 4 bars or 1.5 times maximum working pressure, whichever is higher.
- Overspeed test of all compressor wheels for a duration of 3 minutes at either 20% above alarm level speed at room temperature or 10% above alarm level speed at 45°C inlet temperature when tested in the actual housing with the corresponding pressure ratio. The overspeed test may be waived for forged wheels that are individually controlled by an approved non-destructive method.

4.4 Turbochargers shall be delivered with:

- For category C, PRS certificate which **at a minimum cites the applicable PRS type approval and the ACS, when ACS applies.**
- For category B, a work certificate, which at a minimum cites the applicable type approval, which includes production assessment.

4.5 The same applies to replacement of rotating parts and casing.

4.6 Alternatively to the above periodic product audits, individual certification of a turbocharger and its parts may be made at the discretion of the Society. However, such individual certification of category C turbocharger and its parts shall also be based on test requirements specified **in the above mentioned hyphens points.**

5 ALARMS AND MONITORING

5.1 For all turbochargers of Categories B and C, indications and alarms as listed in the table are required.

5.2 Indications may be provided at either local or remote locations.

Pos.	Monitored Parameters	Category of Turbochargers				Notes
		B		C		
		Alarm	Indication	Alarm	Indication	
1	Speed	High ⁽⁴⁾	X ⁽⁴⁾	High ⁽⁴⁾	X ⁽⁴⁾	
2	Exhaust gas at each turbocharger inlet, temperature	High ⁽¹⁾	X ⁽¹⁾	High	X	High temp. alarms for each cylinder at engine is acceptable ⁽²⁾
3	Lub. oil at turbocharger outlet, temperature			High	X	If not forced system, oil temperature near bearings
4	Lub. oil at turbocharger inlet, pressure	Low	X	Low	X	Only for forced lubrication system ⁽³⁾

(1) For Category B turbochargers, the exhaust gas temperature may be alternatively monitored at the turbocharger outlet, provided that the alarm level is set to a safe level for the turbine and that correlation between inlet and outlet temperatures is substantiated.

- (2) Alarm and indication of the exhaust gas temperature at turbocharger inlet may be waived if alarm and indication for individual exhaust gas temperature is provided for each cylinder and the alarm level is set to a value safe for the turbocharger
- (3) Separate sensors are to be provided if the lubrication oil system of the turbocharger is not integrated with the lubrication oil system of the diesel engine or if it is separated by a throttle or pressure reduction valve from the diesel engine lubrication oil system
- (4) On turbocharging systems where turbochargers are activated sequentially, speed monitoring is not required for the turbocharger(s) being activated last in the sequence, provided all turbochargers share the same intake air filter and they are not fitted with waste gates.

List of amendments effective as of 1 January 2023

<i>Item</i>	<i>Title/Subject</i>	<i>Source</i>
2nd page	M73 Note No.2 added	IACS UR M73
3.2.2	Reference added: 2) a generic range means a series of turbocharger which are of the same design, but scaled to each other.	IACS UR M73
4.4	“as a minimum contain information about relevant PRS Type Approval and ACS when ACS apply.” was changed into “ at a minimum cites the applicable PRS type approval and the ACS, when ACS applies. ”	IACS UR M73
4.6	bullet was changed into hyphens	PRS/editorial