

# **RULES**

PUBLICATION 120/P

## **REQUIREMENTS FOR VESSELS AND UNITS WITH DYNAMIC POSITIONING (DP) SYSTEMS**

**2019**  
July

Publications P (Additional Rule Requirements) issued by Polski Rejestr Statków complete or extend the Rules and are mandatory where applicable.



**GDAŃSK**

*Publication 120/P – Requirements for Vessels and Units with Dynamic Positioning (DP) Systems – July 2019*, is an extension of the requirements contained in the following PRS Rules, in which reference to the *Publication* has been made:

- Part I* – *Classification Regulations of the Rules for the Classification and Construction of Sea-Going Ships*
- Part II* – *Hull*,
- Part III* – *Hull Equipment*
- Part V* – *Fire Protection*
- Part VI* – *Machinery Installations and Refrigerating Plants*
- Part VII* – *Machinery, Boilers and Pressure Vessels*
- Part VIII* – *Electrical Installations and Control Systems*

The *Publication* was approved by the PRS Board on 4 June 2019 and enters into force on 1 July 2019.

# CONTENTS

	page
<b>1 General</b> .....	5
1.1 Purpose .....	5
1.2 Application .....	5
1.3 Definitions .....	5
1.4 Class notations .....	8
1.5 Worst case failure analysis .....	8
1.6 Documentation.....	9
<b>2 Functional Requirements</b> .....	14
2.1 General .....	14
2.2 Power system.....	15
2.3 Thruster system.....	17
2.4 DP control system.....	18
2.5 Cables and auxiliary systems for class notations DP2, DP2+ and DP3 .....	23
2.6 Alarm and Monitoring System .....	24
2.7 Environmental calculation for the DP2+ class notation.....	24
2.8 Software.....	25
2.9 Requirements for essential non-DP systems.....	25
2.10 Independent joystick system.....	25
<b>3 Operational Requirements</b> .....	26
<b>4 Surveys, Testing and Dynamic Positioning Verification Acceptance Document (DPVAD)</b> .....	26
4.1 Surveys and testing .....	26
4.2 Dynamic Positioning Verification Acceptance Document (DPVAD) .....	27



# **1 GENERAL**

## **1.1 Purpose**

The purpose of this *Publication* is to address the design criteria, equipment, operation, testing and documentation requirements for dynamic positioning systems in order to assure that the safety standard of the dynamic positioning system is not less than recommended by the *IMO Circular MSC.1/Circ.1580*.

Compliance with the requirements of this *Publication* shall be documented by means of a Dynamic Positioning Verification Acceptance Document (DPVAD) for the dynamic positioning system.

If PRS exempts any vessel or unit, which embodies features of a novel kind from any of the requirements of this *Publication*, the relevant exemptions shall be listed in the DPVAD.

If alternative design or arrangements have been applied for compliance with any particular provision of this *Publication*, pertinent technical information about the approval should be summarized and annexed to the DPVAD.

## **1.2 Application**

**1.2.1** The present requirements are applicable to vessels and units constructed on or after 9 June 2017.

**1.2.2** For vessels and units constructed on or after 1 July 1994 but before 9 June 2017, the dynamic positioning systems shall fulfil the recommendations specified in *IMO MSC./Circ.645 – Guidelines for Vessels with Dynamic Positioning Systems*, however it is recommended that section 3 *Operational Requirements* of the present *Publication* be applied to all new and existing vessels and units, as appropriate.

**1.2.3** The requirements contained in this *Publication* are additional to those listed in the PRS Rules for the Classification and Construction of Seagoing Ships and should be read in conjunction with the relevant *Parts* of the a/m *Rules*.

**1.2.4** The sea-going ships and mobile offshore units classed with PRS upon compliance with the requirements set forth in this *Publication*, may be assigned the additional class notation (DP1, DP2, DP2+ or DP3), affixed to the symbol of class.

## **1.3 Definitions**

For the purpose of this *Publication*, unless expressly provided otherwise, the terms used herein are defined hereunder:

**1.3.1** **Activity-Specific Operating Guidelines (ASOG)** means guidelines on the operational, environmental and equipment performance limits for the location and specific activity. (For drilling operations, the ASOG may be known as the Well-Specific Operating Guidelines (WSOG)).

**1.3.2** **Bus-tie breaker** means a device connecting/disconnecting switchboard sections ("closed bus-tie(s)" means connected).

**1.3.3** **Company** means the owner of the ship or any other organization or person such as the manager, or the bareboat charterer, who has assumed the responsibility for operation of the ship from the owner of the ship and who on assuming such responsibility has agreed to take over all duties and responsibilities imposed by the International Safety Management Code.

**1.3.4** **Computer system** means a system consisting of one or more computers and associated hardware, software and their interfaces.

**1.3.5** **Consequence analysis** means a software function continuously verifying that the vessel will remain in position even if the worst-case failure occurs.

**1.3.6 Dynamic Positioning control station (DP control station)** means a workstation designated for DP operations, where necessary information sources, such as indicators, displays, alarm panels, control panels and internal communication systems are installed (this includes: DP control and independent joystick control operator stations, required position reference systems' Human Machine Interface (HMI), manual thruster levers, mode change systems, thruster emergency stops, internal communications).

**1.3.7 Dynamic Positioning operation (DP operation)** means using the DP system to control at least two degrees of freedom in the horizontal plane automatically.

**1.3.8 Dynamic Positioning Verification Acceptance Document (DPVAD)** means the document issued by PRS to a DP vessel complying with these requirements.

**1.3.9 Dynamically positioned vessel (DP vessel)** means a unit or a vessel which automatically maintains its position and/or heading (fixed location, relative location or predetermined track) by means of thruster force. **For DP2+ an intact vessel shall be able to keep position and heading without contribution from transverse thrust generated by the combined use of propellers and rudders. For DP2+ thruster force may include propulsion and steering (rudder) forces for back-up purposes only (e.g. after loss of one redundancy group).**

**1.3.10 Dynamic Positioning control system (DP control system)** means all control components and systems, hardware and software necessary to dynamically position the vessel. The DP control system consists of the following:

- .1 computer system/joystick system;
- .2 sensor system(s);
- .3 control stations and display system (operator panels);
- .4 position reference system(s);
- .5 associated cabling and cable routing;
- .6 networks.

**1.3.11 Dynamic Positioning system (DP system)** means the complete installation necessary for dynamically positioning a vessel comprising, but not limited to, the following sub-systems:

- .1 power system;
- .2 thruster system; and
- .3 DP control system.

**1.3.12 Failure** means an occurrence in a component or system that causes one or both of the following effects:

- .1 loss of component or system function; and/or
- .2 deterioration of functional capability to such an extent that the safety of the vessel, personnel or environment protection is significantly reduced.

**For vessels that shall comply with DP2 and DP2+ requirements, certain exceptions will be allowed in the definition of single failure. Flooding and fire shall not be considered beyond main class requirements. Failure of static components, e.g. pipes, manual valves, cables etc. may not need to be considered if adequate reliability of a single component can be documented, and the part is protected from mechanical damage. Specific requirements will apply as given in the following sections of this Publication. Especially for DP2+ failure of a wide range of static components will be considered as relevant single failures.**

**1.3.13 Failure Modes and Effects Analysis (FMEA)** means a systematic analysis of systems and sub-systems to a level of detail that identifies all potential failure modes down to the appropriate sub-system level and their consequences.

**1.3.14 FMEA proving trials** means the test program for verifying the FMEA.

**1.3.15 Hidden failure** means a failure that is not immediately evident to operations or maintenance personnel and has the potential for failure of equipment to perform an on-demand function, such as protective functions in power plants and switchboards, standby equipment, backup power supplies or lack of capacity or performance.

**1.3.16 Joystick system** means a system with centralized manual position control and manual or automatic heading control.

**1.3.17 Loss of position and/or heading** means that the vessel's position and/or heading is outside the limits set for carrying out the DP activity in progress.

**1.3.18 Position keeping** means maintaining a desired position and/or heading or track within the normal excursions of the control system and the defined environmental conditions (e.g. wind, waves, current, etc.).

**1.3.19 Power management system** means a system that ensures continuity of electrical supply under all operating conditions.

**1.3.20 Power system** means all components and systems necessary to supply the DP system with power. The power system includes but is not limited to:

- .1 prime movers with necessary auxiliary systems including piping, fuel, cooling, pre-lubrication and lubrication, hydraulic, pre-heating, and pneumatic systems;
- .2 generators;
- .3 switchboards;
- .4 distribution systems (cabling and cable routing);
- .5 power supplies, including uninterruptible power supplies (UPS); and
- .6 power management system(s) (as appropriate).

**1.3.21 Redundancy** means the ability of a component or system to maintain or restore its function when a single failure has occurred. Redundancy can be achieved, for instance, by the installation of multiple components, systems or alternative means of performing a function.

**1.3.22 Time to safely terminate (operations)** means the amount of time required in an emergency to safely cease operations of the DP vessel.

**1.3.23 Thruster system** means all components and systems necessary to supply the DP system with thrust force and direction. The thruster system includes:

- .1 thrusters with drive units and necessary auxiliary systems including piping, cooling, hydraulic, and lubrication systems, etc.;
- .2 main propellers and rudders if these are under the control of the DP system;
- .3 thruster control system(s);
- .4 manual thruster controls; and
- .5 associated cabling and cable routing.

**1.3.24 Worst-Case Failure Design Intent (WCFDI)** means the specified minimum DP system capabilities to be maintained following the worst-case failure. The worst-case failure design intent is used as the basis of the design. This usually relates to the number of thrusters and generators that can simultaneously fail.

**1.3.25 Worst-Case Failure (WCF)** means the identified single fault in the DP system resulting in maximum detrimental effect on DP capability as determined through the FMEA. **Failure modes related to the class notations as follows:**

- for **DP1**, loss of position may occur in the event of a single fault
- for **DP2+** loss of position is not to occur in the event of a single failure as specified in 2.1.10 and 2.1.11
- for **DP2**, loss of position is not to occur in the event of a single failure as specified in 2.1.12
- for **DP3**, loss of position is not to occur in the event of a single failure as specified in 2.1.13.

## 1.4 Class notations

**1.4.1** The ship or unit depending on the degree of the redundancy of the system may be assigned one of the following additional class notations affixed to the symbol of class:

### DP1

The dynamic positioning system is capable of automatically keeping position and heading, the loss of ship's position or heading may occur in the event of a single fault:

- redundancy of any active or static component is not needed.

This notation meets recommendations of IMO class 1.

### DP2

The dynamic positioning system is capable of automatically keeping position and heading, the loss of ship's position or heading is not to occur in the event of a single fault:

- in any active component or system,
- redundancy of all active components is required (generating sets, distribution system in main switchboards, thrusters, remote controlled valves, etc.),
- in any normally static component which is not properly documented with respect to protection and reliability.

This notation meets recommendations of IMO class 2.

### DP2+

The dynamic positioning system is capable of automatically keeping position and heading, the loss of ship's position or heading is not to occur in the event of a single fault:

- in any active component or system,
- redundancy of all active components is required (generating sets, distribution system in main switchboards, thrusters, remote controlled valves, etc.),
- in any normally static component which is not properly documented with respect to protection and reliability.

Additional requirements to achieve higher availability and endurance compared to DP2 will apply.

This notation meets recommendations of IMO class 2.

### DP3

The dynamic positioning system is capable of automatically keeping position and heading, the loss of position is not to occur in the event of single fault:

- in any active components (as listed for DP2) or systems and any static component of propulsion system,
- in all components of propulsion system in any one watertight compartment (from fire or flooding),
- all components in any one fire sub-division, from fire or flooding (for cables, see also paragraph 2.5).

Redundancy of all components of propulsion systems and its physical separation by location in separate rooms is required.

This notation meets recommendations of IMO class 3.

**1.4.2** When a vessel is assigned DP class notation this means that the DP vessel is suitable for DP operations within the assigned and lower class notations.

## 1.5 Worst case failure analysis

**1.5.1** For class notations DP2, DP2+ and DP3, a single inadvertent act should be considered as a single fault if such an act is reasonably probable.

**1.5.2** Based on the single failure criteria in paragraph 1.4 the worst-case failure should be determined and used as the criterion for the consequence analysis (see paragraph 2.4.2.4 - Computers).



**1.5.3** It is a provision of this *Publication* that the DP vessel is operated in such a way that the worst-case failure, as determined in accordance with paragraph 1.4, can occur at any time without causing a breach of acceptable excursion criteria set for loss of position and/or heading for class notations DP2, DP2+ and DP3.

## 1.6 Documentation

The documentation listed below should be submitted as a complementary to those required for the vessel's mandatory class notation.

**Table 1.6**

System	Document	For Info	Reviewed / approved	To be kept onboard
Dynamic Positioning System	<b>Documents listed in this section are mainly related to the global functionality, performance and characteristics of an integrated DP system.</b>			
	DP Operations Manual		x	x
	System description including a functional diagram		x	
	Details of the DP alarm system and its relations with the main alarm system		x	
	General Arrangement drawing for DP Control Station including control console, control panel, layout of Navigation bridge deck, list of equipment, etc.		x	
	Layout diagram of fire and watertight subdivisions for DP3 requirement of resistance to worst case failure from fire and/or flooding		x	x
	Failure modes and effects analysis (FMEA) for DP2 DP2+ and DP3		x	x
	DP station keeping capability analysis including environmental force calculation, thruster force calculation and capability polar plots for normal operational case and for post Worst Case Failure operational case		x	
	DP system testing plan (quay side and sea trials)		x	x
	Cable routing layout drawing for DP3 (for the different systems cables have to be identified in different colours)		x	
	Specification of environmental conditions (wind and sea) for DP operation with respective DP capability analysis	x		
	Basic design of DP system redundancy (DP2, DP2+ and DP3)		x	
	Description of vessel emergency shutdown (ESD) system if applicable	x		
	Description of emergency disconnecting system (EDS) if applicable	x		
	Planned inspection and maintenance	x		x
	Environmental calculation for DP2+		x	
Documentation of users interfaces (panel views)	x			
Power System	<b>Documents listed in this section are mainly related to the power system including all components and subsystems necessary to supply the DP system with power.</b>			
	Electrical power generation and distribution system		x	
	Electrical power balance		x	
	Auxiliary systems distribution (piping, fuel, cooling, pre-lubrication and lubrication, hydraulic, pre-heating, and pneumatic systems)		x	
	Uninterruptable power, battery and 24V DC supply systems		x	

System	Document	For Info	Reviewed / approved	To be kept onboard
	Bus-tie breaker protective functions (where applicable)		x	
	For <b>DP2</b> , <b>DP2+</b> and <b>DP3</b> a power balance with power demand of the DP system under the specified environmental conditions (wind, wave, current) and after the worst case failure and power demand for the supply of the vessel (basic load)		x	
Thruster System	Thruster system arrangement		x	
	Thruster control system		x	
	Thrust output and power input curves		x	
	Thruster auxiliary system		x	
	Thruster monitoring system		x	
	Description of emergency stop system for thrusters		x	
	Thrust response time for thrust and direction changes	x		
	Thrust reductions due to interaction effects	x		
	Manufacturer test procedure		x	
	DP trial test procedure (quay side and sea trials)		x	x
	Manual for operation and maintenance	x		x
DP Control System	DP Control system, scope and arrangement		x	
	Details of the position reference system and environmental monitoring systems		x	
	Power supply arrangement		x	
	Circuit diagram		x	
	Instrument and equipment list	x		
	Details of the consequence analysis ( <b>DP2</b> , <b>DP2+</b> , <b>DP3</b> )		x	
	Certification of suitability of control equipment for the marine atmosphere	x		x
	Control system functional description	x		
	Manufacturer's equipment operation documents		x	
	Software quality plan	x		
	FMEA test plan of DP control system ( <b>DP2</b> , <b>DP2+</b> , <b>DP3</b> )		x	x
	Manufacturer test procedure		x	x
	DP trial test procedure (quay side and sea trials)		x	x
	Manual for operation and maintenance	x		x
Independent joystick control system	Control system functional description		x	
	Block diagram		x	
	Power supply arrangement		x	
	Details of the position reference system and environmental monitoring systems		x	
	Manufacturer test procedure		x	
	Trial test procedure (quay side and sea trials)		x	x
	Operation manual	x		x
	Documentation of user interface		x	x

System	Document	For Info	Reviewed / approved	To be kept onboard
Thruster control system	Control system functional description		x	
	Block diagram		x	
	User interface documentation		x	x
	Power supply arrangement		x	
	Instrument and equipment list		x	
	Data sheet with environmental specifications		x	
	Software quality plan		x	
	Circuit diagram		x	
	Manufacturer test procedure		x	
	Trial test procedure (quay side and sea trials)		x	x
Operation manual	x		x	
Position reference systems	User interface documentation		x	x
	Power supply arrangement		x	
	Instrument and equipment list		x	
	Data sheet with environmental specifications		x	
	Trial test procedure (quay side and sea trials)		x	x
	Operation manual	x		x
Sensor systems (wind, vertical reference, heading reference, etc)	User interface documentation		x	
	Power supply arrangement		x	
	Instrument and equipment list		x	
	Data sheet with environmental specifications		x	
	Trial test procedure (quay side and sea trials)		x	x
Main electric power system	Electric power balance (Note 1)		x	
Power management system (PMS)	Failure mode and effect analysis (FMEA) for <b>DP2</b> , <b>DP2+</b> and <b>DP3</b>		x	x

Note 1: For dynamic positioning operation. For vessels with the class notation **DP2**, **DP2+** and **DP3** the load calculations shall also reflect the situation after the maximum single failures. May be a part of the power consumption balance.

### 1.6.1 Redundancy concept

With the classification contract for **DP2**, **DP2+** and **DP3** the following DP operation related information has to be provided:

*Redundancy concept document* (FMEA of basic design) with worst case failure design intent including the following information:

- General arrangement (for information)
- Power plant configuration for DP operation (DP2 or DP3-Mode)
- Permissible number of failed thrusters
- Required power sources for DP operation and permissible loss of power sources after one failure.
- Percentage of remaining main power after worst case failure
- Definition of time period for safely terminating a DP operation.

## 1.6.2 Failure Mode and Effect Analysis (FMEA)

Failure Mode and Effect Analysis (FMEA) concerning availability of the DP system after a single failure shall be provided for the class notations **DP2**, **DP2+** and **DP3**, for the desired DP2, DP2+ or DP3 power plant configuration.

DP FMEA shall be performed, based on IEC 60812 or equivalent e.g. (IMCAM166, IMCA M178), according to common DP FMEA industrial requirements.

The results of DP FMEA shall be verified during DP FMEA proving trials.

The relevant test program for DP FMEA proving trial has to be provided for approval.

**1.6.2.1** DP FMEA and DP FMEA test programs are to be kept onboard and they are to be updated to cover subsequent alterations to the DP system hardware or software.

### 1.6.2.2 Failure Mode Analysis

Single failure includes, but is not limited to following:

- All redundant components, systems or subsystems
- A single inadvertent act of operation (ventilation, fire suppression, ESD) where applicable and if such an act is reasonably probable
- Hidden failures (such as protective functions on which redundancy depends) where applicable
- Common failure modes
- Governor and AVR failure modes where applicable
- Main switchboard control power failure modes
- Bus-tie protection where applicable
- Power management system
- DP control system input and output arrangement
- Position reference processing
- Networks
- Communication failure
- Automatic interventions caused by external events, when found relevant (e.g., automatic action upon detection of gas)

The Failure Mode Analysis is also to include:

- The most predictable cause associated with each failure mode
- The method of detecting that the failure has occurred
- The effect of the failure upon the rest of the system's ability to maintain position
- An analysis of possible common failure modes

Where parts of the system are identified as non-redundant and where redundancy is not possible, these parts are to be further studied with consideration given to their reliability and mechanical protection. The results of this further study are to be submitted for review.

When there are more configurations for the diesel electric plant design to cope with equipment unavailability (e.g., failures or equipment taken down for maintenance), it is important that all configurations that are possible to be included in DP operations are to be analysed in the vessel's DP system FMEA to prove that the DP system remains redundant. Fault tolerance of the configurations is to be made visible and understood by the crew.

An FMEA worksheet is to be prepared for each equipment failure assessment. Some pertinent aspects to be included in the worksheets are:

- System name (including main system, system, and subsystem)
- Reference drawings
- Equipment name or number
- Function description
- Operational mode
- Failure modes
- Failure causes
- Failure effects (including local effect and end effect)
- Failure detection

- Corrective action
- Severity of failure effect (providing definitions of categories of severity)
- Remarks

### **1.6.2.3 FMEA Report**

#### **1.6.2.3.1 FMEA Analysis Report**

DP FMEA analysis report is to be sufficiently detailed to cover all the systems associated with the dynamic positioning of the vessel.

DP FMEA analysis report is to be a self-contained document including, but not limited to the following:

- A brief description of the vessel, vessel's worst-case failure design intent and whether the analysis has confirmed or disproved it
- Definitions of the terms, symbols and abbreviations
- Analysis method and assumptions
- A description of all the systems associated with the dynamic positioning of the vessel and a functional block diagram showing their interaction with each other. Such systems would include the DP electrical or computer control systems, electrical power distribution system, power generation, fuel systems, lubricating oil systems, cooling systems, backup control systems, etc.
- System block diagrams are to be included where appropriate
- A description of each physically and functionally independent item and the associated failure modes
- A description of the effects of each failure mode alone on other items within the system and on the overall dynamic positioning system
- Analysis findings and recommendations
- Conclusions including worst case failure and recommended changes
- Recommended FMEA tests

FMEA analysis report is to be updated after major modifications and is to be kept onboard the vessel.

#### **1.6.2.4 FMEA Proving Trial Report**

FMEA proving trial procedure is to be developed as part of FMEA study. The objective of FMEA proving trial is to confirm FMEA analysis findings and also to confirm that essential functions and features upon which the fault tolerance of the DP system depends are functional in so far as it is practical to do so (protections, power management, etc.). The proving trial report is to establish FMEA test list and the corresponding test procedures including but not limited to the following:

- Purpose of test or failure mode
- Vessel and equipment setup
- Test method
- Expected results
- Observed results
- Failure detection
- Failure effects
- Outstanding or resolved action items
- Comments
- Witness name, signature and date for each test

After completion of DP proving trials, the final version of DP FMEA analysis and DP proving trial report, including final analysis/conclusions based on actual results from DP testing, are to be submitted.

### **1.6.3 Documents to be kept on board in case of ship's modifications**

**1.6.3.1** When a vessel is commissioned or following major modifications and additions to the electrical and machinery installations, the documents listed in Table 1.6 which show the final arrangement of the system are to be supplied on board.

## 2 FUNCTIONAL REQUIREMENTS

### 2.1 General

**2.1.1** Insofar as is practicable, all components in a DP system should be designed, constructed and tested in accordance with international standards recognized by PRS.

**2.1.2** If external forces from mission-related systems (cable lay, pipe lay, mooring, etc.) have a direct impact on DP performance, the influence of these systems should be considered and factored into the DP system design. Where available from the DP system or equipment manufacturer, such data inputs should be provided automatically to the DP control system.

Additionally, provisions should be made to provide such data inputs into the DP control system manually. These systems and the associated automatic inputs should be subject to surveys, testing and analysis specified in paragraph 4.1.

**2.1.3** In order to meet the single failure criteria given in paragraph 1.4, redundancy of components will normally be necessary as follows:

- .1 for class notation **DP2**, redundancy of all active components;
- .2 for class notation **DP2+**, redundancy of all active components and specified static components;
- .3 for class notation **DP3**, redundancy of all components and A-60 physical separation of the components.

**2.1.4** For class notations **DP2+** and **DP3**, the DP system shall be designed with redundancy. A position keeping ability shall be maintained without disruption upon any single failure. Full stop of thrusters and subsequent start-up of available thrusters is not considered an acceptable disruption.

**2.1.5** For class notation **DP3**, full redundancy of the control systems may not be possible. (i.e. there may be a need for a single changeover system from the main computer system to the backup computer system). Such connections between otherwise redundant and separated systems may be accepted when these are operated so that they do not represent a possible failure propagation path during DP operations. Failure in one system should in no case be transferred to the other redundant system.

**2.1.6** For class notations **DP2**, **DP2+** and **DP3**, connections between otherwise redundant and separated systems should be kept to a minimum and made to fail to the safest condition. Failure in one system should in no case be transferred to the other redundant system.

**2.1.7** Redundant components and systems should be immediately available without needing manual intervention from the operators and with such capacity that the DP operation can be continued for such a period that the work in progress can be terminated safely. The transfer of control should be smooth and within acceptable limitations of the DP operation(s) for which the vessel is designed.

**2.1.8** For class notations **DP2**, **DP2+** and **DP3**, hidden failure monitoring should be provided on all devices where the FMEA shows that a hidden failure will result in a loss of redundancy.

**2.1.9** For class notations **DP2+** and **DP3**, redundancy shall be based upon running machinery. Automatic or manual intervention arranged to improve the position keeping ability after a failure will be accepted, but cannot be considered by the consequence analysis. Automatic start of equipment may be accepted as contributing to redundancy only if their reliability and simplicity of operation is satisfactory so that they can be brought into operation before position and heading keeping performance is degraded.

**2.1.10** For class notation **DP2+**, the loss of position shall not be allowed to occur in the event of a single failure in any active component or system, nor in any static components as specified in this *Publication*. Single failure criteria for **DP2+** include:

- any active component or system
- static components as specified in this *Publication*

- other static components which are not properly documented with respect to protection
- a single inadvertent act of operation if such act is reasonably probable
- systematic failures or faults that can be hidden until a new fault appears
- automatic interventions caused by external events, when found relevant (e.g. automatic action upon detection of gas).

**2.1.11** The following components/systems are also considered to fail as consequence of a single failure for **DP2+**:

- coolers
- filters
- motorised valves
- fuel oil service tanks and appurtenant piping supplying the engine(s)
- electrical and electronic equipment (this includes all onboard equipment and systems, e.g. any safety shut-down systems (spurious shut down), vessel control systems, etc.)
- when considering single failures of switchboards, the possibility of short-circuit of the bus-bars has to be considered.

**2.1.12** For class notation **DP2** the single failure criteria shall be based on the same criteria as given for **DP2+** in 2.1.10 and 2.1.11. However, based on proper FMEA, static components like coolers, filters and piping/tanks may be considered as not failing.

**2.1.13** For class notation **DP3** loss of position shall not be allowed to occur in the event of a single failure. In addition to the single failures listed 2.1.10 and 2.1.11, the single failure criteria for **DP3** include:

- all static components in the DP system
- all components in any watertight compartment, from fire and flooding
- all components in any one fire-subdivision, from fire or flooding (for cables, see also 2.5).

**2.1.14** The DP control station should be arranged where the operator has a good view of the vessel's exterior limits and the surrounding area. Equipment that should be located at the DP control station includes, but is not limited to:

- .1 DP control and independent joystick control operator stations;
- .2 manual thruster levers;
- .3 mode change systems;
- .4 thruster emergency stops;
- .5 internal communications; and
- .6 position reference systems' HMI, when considered necessary.

## **2.2 Power system**

**2.2.1** The electrical installations are to be designed, constructed and tested according to the relevant applicable class requirements, in particular for:

- .1 rotating machines;
- .2 transformers;
- .3 switchboards;
- .4 electrical cables;
- .5 batteries and/or UPS;
- .6 convertors;
- .7 electronic equipment;

All above equipment is to include its associated auxiliaries and control system and relevant power supply, i.e. electric (24V DC, UPS and batteries), pneumatic, hydraulic, electronic, as applicable. For class notations **DP2**, **DP2+** and **DP3** additional requirements will apply in regard to redundancy and with respect to maximum single failure, as specified for each notation.

**2.2.2** The power system should have an adequate response time to changes in power demand.

**2.2.3** For class notation **DP1**, the power system need not be redundant.

**2.2.4** For class notation **DP2** and **DP2+**, the power system should be divisible into two or more systems so that, in the event of failure of one sub-system, at least one other system will remain in operation and provide sufficient power for station keeping. The power system(s) may be run as one system during operation, but should be arranged by bus-tie breaker(s) to separate the systems automatically upon failures which could be transferred from one system to another, including, but not limited to, overloading and short circuits.

**2.2.5** For class notation **DP3**, the power system should be divisible into two or more systems so that, in the event of failure of one system, at least one other system will remain in operation and provide sufficient power for station keeping. The divided power system should be located in different spaces separated by A-60 class divisions. Where the power systems are located below the operational waterline, the separation should also be watertight. Bus-tie breakers should be open during class notation DP3 operations unless equivalent integrity of power operation can be accepted according to paragraph 2.1.5.

**2.2.6** For class notations **DP2**, **DP2+** and **DP3**, the power available for position keeping should be sufficient to maintain the vessel in position after worst-case failure according to paragraph 1.5.

**2.2.7** For class notation **DP2**, **DP2+** and **DP3** the number of generators shall comply with the redundancy requirements as defined in the single failure criteria in 1.6.2.2.

**2.2.8** For class notations **DP2** and **DP3**, at least one automatic power management system (PMS) should be provided and should have redundancy according to the class notation and a blackout prevention function.

**2.2.9** For class notation **DP2+**, an automatic power management system shall be arranged, operating with both open and closed bus-bar breakers. This system shall be capable of performing the following functions:

- load dependent starting of additional generators,
- block starting of large consumers when there is not adequate running generator capacity,
- and to start up generators as required, and hence to permit requested consumer start to proceed,
- if load dependent stop of running generators is provided, facilities for disconnection of
- this function shall be arranged.

**2.2.10** Alternative energy storage (e.g. batteries and fly-wheels) may be used as sources of power to thrusters as long as all relevant redundancy, independency and separation requirements for the relevant notation are complied with. For class notations **DP2**, **DP2+** and **DP3**, the available energy from such sources may be included in the consequence analysis function required in paragraph 2.4.3.4 when reliable energy measurements can be provided for the calculations.

**2.2.11** Sudden load changes resulting from single faults or equipment failures should not create a blackout.

**2.2.12** For class notations **DP2**, **DP2+** and **DP3**, the following applies:

- .1 the power available for position keeping is to be sufficient to maintain the ship in position after the worst case failure occurring, as specified in 1.3.25;
- .2 a power management system (PMS) is to be provided and is to be redundant in such a way the failure of the power management system is not to produce a failure exceeding the worst case failure of 1.3.25, to be demonstrated through FMEA. A failure in the power management system is to initiate an alarm in the DP control station.  
For **DP3**, the requirements as per .1 and .2 above are to be complied with also in case of fire or flooding in one compartment.



**2.2.13** The power management system is to be continuously supplied by means of an uninterruptible power supply system (UPS). Where power management system is required to be redundant, the redundancy is to be achieved also by the relevant power supply.

**2.2.14** The power management system is to be capable of:

- .1 enabling quick supply of active power to consumers in all operating conditions, including generator failure or change of thruster configuration;
- .2 maintaining a proper balance between power demand and power generating configuration,
- .3 disconnecting or reducing automatically the excess load in case of inadequate available power in order to maintain power to thrusters.

**2.2.15** A failure in a power management system shall not cause alteration to the power generation, and shall initiate an alarm in the main DP-control centre.

**2.2.16** It shall be possible to operate the switchboards in manual as required for the main class, with the power management system disconnected.

**2.2.17** When generators in different redundancy groups are running in parallel, as accepted for **DP2** and **DP2+**, this will introduce the possibility that a single failure may propagate between systems. In such cases it is required that protective measures are implemented in the system in order to ensure the required integrity between the redundancy groups. Analysis of relevant failure modes shall be addressed in the FMEA.

**2.2.18** For class notation **DP2**, **DP2+** and **DP3** the switchboard arrangement shall be such that no single failure will give a total black-out. For **DP2** and **DP2+** this means equipment failures. For **DP3** this means failure of all equipment in any fire and/or watertight subdivision.

### **2.3 Thruster system**

**2.3.1** Each thruster on a DP system should be capable of being remote-controlled individually, independently of the DP control system.

**2.3.2** The thruster system should provide adequate thrust in longitudinal and lateral directions, and provide yawing moment for heading control.

**2.3.3** For class notation **DP2+** the thruster configuration shall include thrust units which together will produce, at any time, transverse and longitudinal thrust, and a yawing moment. When intact, the DP system shall be able to produce such combined forces without contribution from transverse thrust generated by the combined use of propellers and rudders. Transverse thrust generated by the combined use of propellers and rudders will not be considered as “thrust units” in this context.

**2.3.4** For class notations **DP2** and **DP3**, the thruster system should be connected to the power system in such a way that paragraph 2.3.2 can be complied with even after failure of one of the constituent power systems and the thrusters connected to that system.

**2.3.5** The values of thruster force used in the consequence analysis (see paragraph 2.4.3.4) should be corrected for interference between thrusters and other effects which would reduce the effective force.

**2.3.6** Failure of a thruster system including pitch, azimuth and/or speed control, should not cause an increase in thrust magnitude or change in thrust direction.

**2.3.7** Individual thruster emergency stop systems should be arranged in the DP control station. For class notations **DP2**, **DP2+** and **DP3**, the thruster emergency stop system should have loop monitoring. For class notation **DP2+**, an alarm shall be initiated upon loop failure. For class notation **DP3**, the effects of fire and flooding should be considered.

## 2.4 DP control system

### 2.4.1 General

- .1 In general, the DP control system should be arranged in a DP control station where the operator has a good view of the vessel's exterior limits and the surrounding area.
- .2 The DP control station should display information from the power system, thruster system and DP control system to ensure that these systems are functioning correctly. Information necessary to safely operate the DP system should be visible at all times. Other information should be available upon the operator's request.
- .3 Display systems and the DP control station in particular should be based on sound ergonomic principles which promote proper operation of the system. The DP control system should provide for easy accessibility of the control mode, i.e. manual joystick, or automatic DP control of thrusters, propellers and rudders, if part of the thruster system. The active control mode should be clearly displayed.
- .4 For class notations **DP2**, **DP2+** and **DP3**, operator controls should be designed so that no single inadvertent act on the operator's panel can lead to a loss of position and/or heading.
- .5 For class notation **DP2+**, it shall be possible to control the thrusters manually by a common joystick in the main DP-control system from all operator stations.
- .6 The DP-control centre is the main control station for equipment in the DP-control system which requires manual operation.
- .7 Alarms and warnings for failures in all systems interfaced to and/or controlled by the DP control system should be audible and visual. A record of their occurrence and of status changes should be provided together with any necessary explanations.
- .8 Sensors and/or reference systems may be shared with other systems provided failure in any of the other systems cannot spread to the DP system.
- .9 The DP control system should prevent failures being transferred from one system to another. The redundant components should be so arranged that any failed component or components may be easily isolated so that the other component(s) can take over smoothly with no loss of position and/or heading.
- .10 It should be possible to control the thrusters manually, by individual levers and by an independent joystick, in the event of failure of the DP control system. If an independent joystick is provided with sensor inputs, failure of the main DP control system should not affect the integrity of the inputs to the independent joystick.
- .11 The thruster control modes, i.e. manual, independent joystick and automatic, shall be selectable by a simple device located in the DP-control centre. The control mode selector system may consist of a single selector switch or individual selectors for each thruster.
- .12 For class notations **DP2**, **DP2+** and **DP3**, mode selection systems shall not violate redundancy requirements.
- .13 A dedicated UPS should be provided for each DP control system (i.e. minimum one UPS for class notation **DP1**, two UPSs for class notation **DP2** and **DP2+**, three UPSs for class notation **DP3**) to ensure that any power failure will not affect more than one computer system and its associated components. The reference systems and sensors should be distributed on the UPSs in the same manner as the control systems they serve, so that any power failure will not cause loss of position keeping ability. An alarm should be initiated in case of loss of charge power. UPS battery capacity should provide a minimum of 30 minutes operation following a main supply failure.

For class notations **DP2**, **DP2+** and **DP3**, the charge power for the UPSs supplying the main control system should originate from different power systems.
- .14 The software should be produced in accordance with an appropriate international quality standard recognized by PRS.

## 2.4.2 Arrangement

### 2.4.2.1 Class notation **DP1** shall include:

- an automatic position control mode
- an independent joystick system with automatic heading control
- manual levers for each thruster.

### 2.4.2.2 Class notations **DP2** and **DP2+** shall include:

- an automatic position control mode consisting of at least two mutually independent control systems
- an independent joystick system with automatic heading control
- manual levers for each thruster.

### 2.4.2.3 Notation **DP3** shall include:

- an automatic position control mode consisting of at least two mutually independent control systems
- an independent joystick system with automatic heading control
- manual levers for each thruster
- an automatic back-up positioning control system.

## 2.4.3 Computers

- .1 For class notation **DP1**, the DP control system need not be redundant.
- .2 For class notation **DP2** and **DP2+**, the DP control system should consist of at least two computer systems so that, in case of any single failure, automatic position keeping ability will be maintained. Common facilities such as self-checking routines, alignment facilities, data transfer arrangements and plant interfaces should not be capable of causing failure of more than one computer system. An alarm should be initiated if any computer fails or is not ready to take control.
- .3 For class notation **DP3**, the main DP control system should consist of at least two computer systems arranged so that, in case of any single failure, automatic position keeping ability will be maintained. Common facilities such as self-checking routines, alignment facilities, data transfer arrangements and plant interfaces should not be capable of causing failure of more than one computer system. The two or more computer systems mentioned above do not include the backup computer system; thus, in addition, one separate backup DP control system should be arranged, see paragraph 2.4.2.6. An alarm should be initiated if any computer fails or is not ready to take control.
- .4 For class notations **DP2**, **DP2+** and **DP3**, the DP control system should include a software function, normally known as "consequence analysis", which continuously verifies that the vessel will remain in position even if the worst-case failure occurs. This analysis should verify that the thrusters, propellers and rudders (if included under DP control) that remain in operation after the worst-case failure can generate the same resultant thruster force and moment as required before the failure. The consequence analysis should provide an alarm if the occurrence of a worst-case failure were to lead to a loss of position and/or heading due to insufficient thrust for the prevailing environmental conditions (e.g. wind, waves, current, etc.). For operations which will take a long time to safely terminate, the consequence analysis should include a function which simulates the remaining thrust and power after the worst-case failure, based on input of the environmental conditions.
- .5 Redundant computer systems should be arranged with automatic transfer of control after a detected failure in one of the computer systems. The automatic transfer of control from one computer system to another should be smooth with no loss of position and/or heading.
- .6 For class notation **DP3**, the backup DP control system should be in a room separated by an A-60 class division from the main DP control station. During DP operation, this backup control system should be continuously updated by input from at least one of the required sets of sensors, position reference system, thruster feedback, etc. and be ready to take over control. The switchover of control to the backup system should be manual, situated on the backup

computer, and should not be affected by a failure of the main DP control system. Main and backup DP control systems should be so arranged that at least one system will be able to perform automatic position keeping after any single failure.

- .7 Each DP computer system should be isolated from other on-board computer systems and communications systems to ensure the integrity of the DP system and command interfaces. This isolation may be effected via hardware and/or software systems and physical separation of cabling and communication lines. Robustness of the isolation should be verified by analysis and proven by testing. Specific safeguards should be implemented to ensure the integrity of the DP computer system and prevent the connection of unauthorized or unapproved devices or systems.

#### 2.4.4 Data communication links

- .1 Data communication link used by two or more thrusters and their manual controls shall be designed with redundancy.
- .2 The independent joystick may share the redundant communication link described in 2.4.4.1 with the manual control, but not with the DP-control system.
- .3 When the DP-control system uses a data communication link, this link shall be separate from the communication link(s) for manual control.
- .4 The communication link for the DP-control system shall be arranged with redundancy **DP2** and **DP2+**, and with redundancy and physical separation for **DP3**.
- .5 For **DP2** and **DP2+** control cables and communication links belonging to different redundancy groups should be separated as far as practically possible.

#### 2.4.5 Position reference systems

- .1 Position reference systems should be selected with due consideration to operational requirements, both with regard to restrictions caused by the manner of deployment and expected performance in working situations.
- .2 When more than one positioning reference system is required, then each shall be independent with respect to signal transmission and interfaces.
- .3 For class notation **DP1**, at least two independent position reference systems should be installed and simultaneously available to the DP control system during operation.
- .4 For class notations **DP2** and **DP3**, at least three independent position reference systems should be installed and simultaneously available to the DP control system during operation.
- .5 For class notations **DP2**, **DP2+** and **DP3**, interfaces to the dynamic positioning computer system shall be in accordance with the overall redundancy requirement. Systems should be equally distributed between the redundant groups, and so arranged that systems based on the same principle are equally distributed between the redundant groups.
- .6 When two or more position reference systems are required, they should not all be of the same type, but based on different principles and suitable for the operating conditions.
- .7 The position reference systems should produce data with adequate accuracy and repeatability for the intended DP operation.
- .8 The performance of position reference systems should be monitored and warnings should be provided when the signals from the position reference systems are either incorrect or substantially degraded.
- .9 For class notation **DP3**, at least one of the position reference systems should be connected directly to the backup control system and separated by an A-60 class division from the other position reference systems.
- .10 When acoustic position references are used, hydrophone is to be chosen for minimising influence of mechanical and acoustical disturbance on the transmission channels, such as propeller noise, spurious reflection on the hull, interference of riser, bubble or mud cluster on the acoustic path. The directivity of transponders and hydrophones is to be compatible with the availability of the transmission channels in all foreseeable operational conditions. It is to

be possible to select the frequency range and the rate of interrogation according to prevailing acoustical conditions, including other acoustical system possibly in service in the area.

- .11 When taut wires system is used, materials used for wire rope, tensioning and auxiliary equipment are to be appropriate for marine service. The anchor weight is to be designed to avoid dragging on the sea floor and is not to induce, on recovery, a wire tension exceeding 60% of its breaking strength, and the capacity of the tensioner is to be adapted to the expected movement amplitude of the unit.
- .12 When a GPS or DGPS is used, it is to be designed according to IMO resolutions A.525(13), A.694(17), A.813(19) for communication and performance standards. The equipment is to be either type approved or MED, or accepted by the Flag Administration, as applicable,. The relevant certificates are to be ready available and in course of validity. For other reference systems the principle of equivalency is applied.
- .13 For class notation **DP2+**, at least two of the positioning reference systems' HMIs are to be independent of the DP-control system. These HMIs are to be placed at the main DP-control centre in view of the DP operator. The two reference systems fulfilling this requirement shall have their power supply from different UPSs.
- .14 Power supply to the position reference systems shall be from UPS. For DP2, DP2+ and DP 3 arrangement of power supplies shall be in accordance with the redundancy requirement.

#### 2.4.6 Vessel sensors

- .1 Vessel sensors should at least measure vessel heading, vessel motions and wind speed and direction.
- .2 When a class notation **DP2**, **DP2+** or **DP3** DP control system is fully dependent on correct signals from vessel sensors, these signals should be based on three systems serving the same purpose (i.e. this will result in at least three heading reference sensors being installed).
- .3 Sensors for the same purpose which are connected to redundant systems should be arranged independently **with respect to power, signal transmission, and interfaces**. so that failure of one will not affect the others. **For class notations DP2, DP2+ and DP3 arrangement of power supply shall be in accordance with the overall redundancy requirement. For DP1 class notation where only UPS is required power may be taken from the same distribution/UPS.**
- .4 For class notation **DP3**, one of each type of sensor should be connected directly to the backup DP control system, and should be separated by an A-60 class division from the other sensors. If the data from these sensors is passed to the main DP control system for their use, this system should be arranged so that a failure in the main DP control system cannot affect the integrity of the signals to the backup DP control system.

**Table 2.4**  
**Summary of DP System requirements for PRS DP Notations**

Subsystems or components	Equipment	Minimum Requirements for each Class Notation			
		DP1	DP2	DP2+	DP3
POWER SYSTEM	Generators and Prime Movers	Non-redundant	Redundant	Redundant	Redundant, in separate compartments.
	Main switchboard	1 See note (*)	1 with 2 busbars connected by normally closed 1 bus-tie	1 with 2 busbars connected by normally closed 1 bus-tie	At least 2 with bus-ties arranged in separate compartments
	Bus-tie breaker	0 See note (*)	1	1	2 2 kept open, one in each main switchboard
	Distribution system	Non-redundant. See note (*)	Redundant arrangement	Redundant arrangement	Redundant arrangement in separate compartments
	Power management system (PMS)	No	Yes	Yes	Yes
THRUSTER SYSTEM	Thrusters	Non-redundant	Redundant arrangement	Redundant arrangement	Redundant arrangement in separate compartments
	Single levers for each thruster at main DP control centre	Yes	Yes	Yes	Yes
DP-CONTROL SYSTEM	Number of Control Computers	1	2	2	2 + 1 in backup control station
	Joystick with automatic heading	Required See note (**)	Required	Required	Required
	Manual Thruster Control	Yes	Yes	Yes	Yes
REFERENCE SYSTEM	Position Reference system	2	3	3	2 + 1 in backup control station
	HMI for position reference systems required outside DP control system operator station(s)	No	No	Yes	No
	VRS/MRU	1	2	3	2 + 1 in backup control station
	Wind sensor	1	2	2	2 + 1 in backup control station
	Gyro	1	3	3	2 + 1 in backup control station
UPS UNIT		1	2	2	2 + 1 in separate compartment
Printer		Yes	Yes	Yes	Yes
Backup Control Station for Backup Unit		N/A	N/A	N/A	Yes
Loop monitoring emergency stop loop		No	No	Yes	No
Steering gear – additional monitoring requirements		No	No	Yes	Yes
Consequence Analyzer		No	Yes	Yes	Yes
FMEA		No	Yes	Yes	Yes
(*) According to Rules for Classification and Construction of the Sea-Going Ships, Part VIII. (**) Where provided failure of the joystick is to bring the system in a safe situation.					

## 2.5 Cables and auxiliary systems for class notations DP2, DP2+ and DP3

2.5.1 The auxiliary systems, serving machinery, thrusters, electrical components and all other systems and components necessary for supplying the DP system with power and/or thrust, shall be arranged in accordance with the redundancy requirements as given for these notations.

2.5.2 For DP2+, unless otherwise specified in this *Publication*, fixed piping may be shared by components designed with redundancy.

2.5.3 The fuel oil supply shall be arranged with full separation between systems providing required redundancy, in view of the risk of fuel oil contamination.

2.5.4 There shall be at least one service tank serving each dedicated system. Cross-over facilities may be arranged, but must, if arranged, be kept closed in normal operation.

2.5.5 If the fuel system requires heating, then the heating system shall be designed with the appropriate level of redundancy unless fuel which do not require heating, are arranged so that the requirement in 2.5.4 is fulfilled. ~~Separation by A-60 class division is required for DP3.~~

2.5.6 For DP2+, fresh water cooling systems providing the required redundancy shall be arranged as separated systems, in view of the risk of severe loss of water or accumulation of gas due to leakage.

2.5.7 For DP2+, pneumatic systems providing the required redundancy shall be arranged as separated systems, in view of the risk of leakage.

2.5.8 For DP2, piping systems for fuel, lubrication, hydraulic oil, cooling water and cables should be located with due regard to fire hazards and mechanical damage. Flooding and fire shall not be considered beyond main class requirements.

2.5.9 For DP3, redundant piping systems (e.g. piping for fuel, cooling water, lubrication oil, hydraulic oil, etc.) should not be routed together through the same compartments. The systems that form the designed redundancy requirement shall be separated by a A-60 class division fire -insulated in a proper way, and moreover watertight if placed below the damage water line. Watertight division shall be considered also above the damage water line where large quantity of liquids may occur as a consequence of a leakage, especially in case of flammable liquid leakage possibility.

Where this is unavoidable, such pipes may run together in ducts of A-60 class, the termination of the ducts included, which are effectively protected from all fire hazards except that represented by the pipes themselves. Cables in separate pipes that are separately routed are acceptable on open-deck.

2.5.10 For DP3, cables for redundant equipment or systems should not be routed together through the same compartments. Where this is unavoidable, such cables may run together in cable ducts of A-60 class, the termination of the ducts included, which are effectively protected from all fire hazards except that represented by the cables themselves. Cable connection boxes may not be provided within such ducts.

2.5.11 For DP3, cables for redundant equipment or systems are not to be routed through the same compartments. However, electrical cables of one system may be considered to remain operational if routed through the compartment of the other redundant system, provided that:

- .1 the cables of redundant systems are not routed together;
- .2 the cables comply with standard IEC 60092-359, in order to be considered operational during a flooding scenario, and they have no connections, no joints, no equipment connected to them within the space; if connections, joints and devices are fitted, they are to have a degree of protection IPX8 in accordance with standard IEC 60529, and
- .3 the cables are fire-resistant type complying with standards IEC 60331-1 and IEC 60331-2 and they have no connections, joints and equipment connected to them within the space or, alternatively, they are contained in a trunk closed at all boundaries constructed to "A-60" standard.

## 2.6 Alarm and Monitoring System

2.6.1 An alarm and monitoring system is to be provided in accordance with the applicable requirements of Rules for the Classification and Construction of the Sea-Going Ships, Part VIII.

2.6.2 The DP-control centre shall receive alarms and warnings reflecting the status of the DP system.

2.6.3 An alarm shall be initiated when the vessel exceeds pre-set position and heading limits.

2.6.4 Any failure of an online or standby positioning control system, sensor or positioning reference system selected, shall initiate an alarm.

2.6.5 Consequence analysis for **DP2**, **DP2+** and **DP3** notations:

2.6.5.1 The DP-control systems shall perform an analysis of the ability to maintain position after worst case failures. An alarm shall be initiated, with a maximum delay of 5 minutes, when a failure will cause loss of position in the prevailing weather conditions.

2.6.5.2 The consequence analysis shall be repeated automatically at pre-set intervals. The operator shall be able to monitor that the analysis is in progress.

2.6.5.3 The analysis shall have a lower priority than the control and alarm tasks. If the analysis is not completed within 2 minutes then an alarm shall be initiated.

## 2.7 Environmental calculation for the DP2+ class notation

2.7.1 Environmental calculation shall be submitted for approval for **DP2+** class notation. The position holding performance shall be quantified according to the recognized standard. The calculations shall be presented in form of a report, which shall include the following information as a minimum:

- thruster data: maximum thrust, location, power,
- vessel data used in the calculations to be presented as numerical values together with (simplified) layout drawings showing both projected frontal and lateral areas affected by wind and current. Information about length (overall and LBP), breadth, draught shall also be given,
- calculation: description of mathematical method used in the calculations. Tables giving information for each calculated point: environmental forces for wind, wave and current. Thrust output for each thruster, total thruster force and total turning moment.
- conclusion.

**Table 2.6**  
**Summary of minimum instrumentation at DP Control Station**

System	Monitored Parameters	Indicator	Alarm
Power Distribution System	Status of automatically controlled circuit breakers	x	
	Bus bar current and power levels	x	
	High power consumers – current levels	x	
	Status of power management system	x	x
	Spinning reserve	x	
	Engine lubricating oil pressure – low		x
	Engine coolant temperature – high		x
	CPP hydraulic oil pressure – low and high		x
	CPP hydraulic oil temperature – high		x
	CPP pitch	x	
	Thruster RPM	x	



System	Monitored Parameters	Indicator	Alarm
Thruster Power System	Thruster direction	x	
	Thruster motor/semiconductor converter coolant leakage		x
	Thruster motor semiconductor converter temperature	x	
	Thruster motor short circuit		x
	Thruster motor exciter power available	x	
	Thruster motor supply power available	x	
	Thruster motor overload		x
	Thruster motor high temperature		x
	Thruster operation (on-line/off-line)	x	
System Performance	Excursion outside operating envelope		x
	Control system fault		x
	Position sensor fault		x
	Vessels target and present position and heading	x	
	Wind speed and direction	x	
	Selected reference system	x	
Specific Requirements for DP2 & DP3	Thruster location (pictorial)	x	
	Available thrust used and thrust vector	x	
	Available thrusters on stand-by	x	
	Consequence analyser alert		x
	Position information of individual position reference systems connected	x	

## 2.8 Software

**2.8.1** The software is to comply with requirements of *PRS Publication 9/P*, p.3.1, 3.3 and 3.4.

### 2.9 Requirements for essential non-DP systems

For class notations **DP2**, **DP2+** and **DP3**, systems not directly part of the DP system, but which in the event of failure could cause failure of the DP system (e.g. common fire suppression systems, engine ventilation, heating, ventilation and air conditioning (HVAC) systems, shutdown systems, etc.), should also comply with relevant requirements of this *Publication*.

### 2.10 Independent joystick system

**2.10.1** A joystick system independent of the automatic DP control system should be arranged. The power supply for the independent joystick system (IJS) is to be independent of the DP control system UPSs. An alarm should be initiated upon failure of the IJS.

**2.10.2** The IJS should have automatic heading control.

**2.10.3** Any failure causing operator loss of control of the thrusters in the independent joystick control system shall freeze the thrust commands or set the thrust commands to zero. If the failure affects only a limited number of thrusters, the command to these affected thrusters may be set to zero, while keeping the other unaffected thrusters in joystick control.

### 3 OPERATIONAL REQUIREMENTS

**3.1** Before every DP operation, the DP system should be checked according to applicable vessel specific location checklist(s) and other decision support tools such as ASOG in order to make sure that the DP system is functioning correctly and that the system has been set up for the appropriate mode of operation.

**3.2** During DP operations, the system should be checked at regular intervals according to the applicable vessel-specific watchkeeping checklist.

**3.3** DP operations necessitating class notation **DP2**, **DP2+** or **DP3** should be terminated when the environmental conditions (e.g. wind, waves, current, etc.) are such that the DP vessel will no longer be able to keep position if the single failure criterion applicable to the class notation should occur. In this context, deterioration of environmental conditions and the necessary time to safely terminate the operation should also be taken into consideration. This should be checked by way of environmental envelopes if operating in class notation **DP1** and by way of an automatic means (e.g. consequence analysis) if operating in class notation **DP2**, **DP2+** or **DP3**.

**3.4** The necessary operating instructions should be kept on board.

**3.5** DP capability polar plots should be produced to demonstrate position keeping capacity for fully operational and post worst-case single failure conditions. The capability plots should represent the environmental conditions in the area of operation and the mission-specific operational condition of the vessel.

**3.6** The following checklists, test procedures, trials and instructions should be incorporated into the vessel-specific DP operations manuals:

- .1 location checklist (see paragraph 3.1);
- .2 watchkeeping checklist (see paragraph 3.2);
- .3 DP operating instructions (see paragraph 3.4);
- .4 annual tests and procedures (see paragraph 4.1.1.3);
- .5 initial and periodical (5-year) tests and procedures (see paragraphs 4.1.1.1 and 4.1.1.2);
- .6 examples of tests and procedures after modifications and non-conformities (see paragraph 4.1.1.4);
- .7 blackout recovery procedure;
- .8 list of critical components;
- .9 examples of operating modes;
- .10 decision support tools such as ASOG; and
- .11 capability plots (see paragraph 3.5).

### 4 SURVEYS, TESTING AND DYNAMIC POSITIONING VERIFICATION ACCEPTANCE DOCUMENT (DPVAD)

#### 4.1 Surveys and testing

**4.1.1** Each DP vessel to which the requirements apply should be subject to the surveys and testing specified below:

- .1 an initial survey which should include a complete survey of the DP system and FMEA proving trials for class notations **DP2**, **DP2+** and **DP3** to ensure full compliance with the applicable parts of the requirements. Furthermore it should include a complete test of all systems and components and the ability to keep position after single failures associated with the assigned class notation. The type of tests carried out and results should be recorded and kept on board;
- .2 a periodical testing at intervals not exceeding five (5) years to ensure full compliance with the applicable parts of the requirements. A complete test should be carried out as required in paragraph 4.1.1.1. The type of tests carried out and results should be recorded and kept on board;

- .3 an annual survey should be carried out within three (3) months before or after each anniversary date of the Dynamic Positioning Verification Acceptance Document<sup>1</sup>. The annual survey should ensure that the DP system has been maintained in accordance with applicable parts of the requirements and is in good working order. The annual test of all important systems and components should be carried out to document the ability of the DP vessel to keep position after single failures associated with the assigned class notation and validate the FMEA and operations manual. The type of tests carried out and results should be recorded and kept on board; and
- .4 a survey, either general or partial according to circumstances, should be carried out every time a defect is discovered and corrected or an accident occurs which affects the safety of the DP vessel, or whenever any significant repairs or alterations are made. After such a survey, necessary tests should be carried out to demonstrate full compliance with the applicable provisions of the requirements. The type of tests carried out and results should be recorded and kept on board.

**4.1.2** For class notations **DP2**, **DP2+** and **DP3**, an FMEA should be carried out. This is a systematic analysis of the systems to the level of detail required to demonstrate that no single failure will cause a loss of position or heading and should verify worst-case failure design intent. This analysis should then be confirmed by FMEA proving trials. The FMEA and FMEA proving trials result should be kept on board and the FMEA should be kept updated so that it remains current.

**4.1.3** These surveys and tests should be witnessed by PRS surveyors.

**4.1.4** After any survey and testing has been completed, no significant change should be made to the DP system without the sanction of PRS, except the direct replacement of equipment and fittings for the purpose of repair or maintenance.

## **4.2 Dynamic Positioning Verification Acceptance Document (DPVAD)**

**4.2.1** Compliance with these requirements should be verified by a DPVAD issued by PRS.

**4.2.2** A DPVAD should be issued, after survey and testing in accordance with these requirements, by the PRS.

**4.2.3** The DPVAD should be drawn up in the official language of the issuing country. If the language used is neither English nor French, the text should include a translation into one of these languages.

**4.2.4** The DPVAD is issued for a period not exceeding five years, or for a period specified by the PRS.

**4.2.5** The DPVAD should cease to be valid if significant alterations have been made in the DP system equipment, fittings, arrangements, etc. specified in the requirements without the sanction of PRS, except the direct replacement of such equipment or fittings for the purpose of repair or maintenance.

**4.2.6** The DPVAD issued to a DP vessel should cease to be valid upon transfer of such a vessel to the flag of another country.

**4.2.7** The privileges of the DPVAD may not be claimed in favour of any DP vessel unless the DPVAD is valid.

**4.2.8** Results of the DPVAD tests should be readily available on board for reference.

---

### List of amendments effective as of 1 July 2019

<i>Item</i>	<i>Title/Subject</i>	<i>Source</i>
<a href="#">A lot of items</a>	Implementation of new class notation DP2+	PRS

---

<sup>1</sup> If a Dynamic Positioning Verification Acceptance Document is not available, the anniversary date of the initial survey should be used to determine the date of the annual survey.